



PVC COMPOUNDS

FOR LOW VOLTAGE POWER

Code	Features									Classification					Specific Application	
	Flexible at low temperature	Flame retardant	Flexible	Halogenated	Low Halogen content	High temp resistant	Low temp resistant	Low smoke	Oil resistant	UV resistant	Thermoplastic	Extrusion	Energy	Insulation		Bedding
RDF/85A				•						•	•	•	•		•	-
RDB/85A				•						•	•	•	•		•	-
RDB/85C				•						•	•	•	•		•	-
RDT/85A				•						•	•	•	•		•	Anti-termite
RDT/85R				•						•	•	•	•		•	Anti-rodents
CAI/90A				•						•	•	•	•		•	PVC crystal
RGF/85K				•						•	•	•	•		•	LOI 24%
ICI/80C				•						•	•	•	•		•	LOI 25%
ICI/80T		•		•						•	•	•	•		•	LOI 32%
RGF/85L		•		•						•	•	•	•		•	LOI 30%
RDC/80L				•						•	•	•	•		•	-
ISI/90A				•						•	•	•	•		•	Oil resistance
ISSO/85A		•		•						•	•	•	•		•	LOI 29%
LOI/40F		•			•					•	•	•	•		•	LOI 36%
ICE/87A		•			•					•	•	•	•		•	LOI 30%
ICI/83A		•			•			•	•	•	•	•	•		•	LOI 36%
AAB/89A	•			•		•				•	•	•	•		•	-
AAB/75A	•			•		•				•	•	•	•		•	-
REC/80A	•		•	•			•		•	•	•	•	•		•	-
RGB/80A	•		•	•						•	•	•			•	-
RGB/79A			•	•						•	•	•			•	-
E EI/75A			•	•						•	•	•			•	-
E EI/71A			•	•						•	•	•			•	-
EOC/85A				•						•	•	•		•		-
BEP 2000				•						•	•	•		•		Bedding fo high density
EOA/85A				•						•	•	•		•		-

For more information, please contact our sales department at sales@cabopol.com